

HDcctv H.264 Digital Video Recorders with 1080P HDMI Output


- XHD-04: 4 Channel Video, 48fps @ 1280*720
- XHD-08: 8 Channel Video, 120fps @ 1280*720
- XHD-16: 16 Channel Video, 192fps @ 1280*720



Features

- 720P (1280 x 720) Resolution Recording
- H.264 Compression provides smaller file size & lower bandwidth
- 1 080p HDMI output & simultaneous VGA output and Real Time Live View
- QUADPLEX: Allows simultaneous live view or playback while still continuing to record, network transfer, and back up data.
- 4 (16) Audio Input, 1 Audio Output
- 4 /8/16 Sensor Input, 1/2/4 Alarm Output.
- 1 eSata port for expanding Storage.
- 1 RS-485 for Camera Control.
- 2 USB 2.0 port for backup of recorded files, firmware upgrade, configuration export/import, or USB mouse.
- Individual channel operation such as FPS, quality, recording mode, & detection zone
- Network hardware supports 10/100/1000 Mbps.
- Various network access: Network client SW, Web-viewer, Smartphone APP, and Free 256 Channel CMS.
- Remote access via PC, MAC®, or smartphones such as the iPhone®, Android™, and BlackBerry™.
- Recording priority programmable per channel for schedule, alarm, motion, or continuous.
- Free CMS software included for remote playback, local recording, backup, and remote setting.
- Free DDNS server for use with Dynamic IP addresses.
- Dual-stream support for simultaneous access from a PC, MAC, and/or a cell phone at low bandwidth.
- Bandwidth control
- E-mail event notification, along with image file attachment.
- Covert Channel.
- NTP (Network Time Protocol).
- Watermark Verification.
- Synchronized audio for court evidence.
- Time Stamp over backup data for court evidence.
- Easy and various data backup via DVD, USB flash drive, USB external HDD, and network
- HDD S.M.A.R.T status check and alert via e-mail or internal beep.
- USB Mouse, IR Remote Control.
- 2 internal SATA port HDD storage up to 4TB.
- Multi OSD languages.
- Made in Korea

Rear Info



			4CH	8CH	16CH
Video	Input	Channel Input Level	4CH HDcctv	8CH HDcctv	16CH HDcctv
		Video Loss Check	YES		
	Output	Main Monitor Output	1 HDMI (1080P)		
		Sub Monitor Output	1 VGA (1080P)		
		HD-SDI Output	-	-	1
Audio	Input and Output		4CH In / 1CH Out	4CH In / 1CH Out	16CH In / 1CH Out
	Audio Codec		G.711		
Alarm	Sensor Input		4CH	8CH	16CH
	Alarm Out		1CH	2CH	4CH
Record	Compression		H.264		
	Multi Operation		Quadplex (Playback, Recording, Backup, Netw ork)		
	Resolution		1920*1080, 1280*720, 640*360		
	Recoding Quality Grade		5 Levels		
	Recording Mode		Continuous, Schedule, Motion, Sensor, Manual		
	Motion Detection		Setup by Grid		
	Pre Recording		15 Seconds to 20 Minutes		
	Post Recording		10 Seconds to 60 Seconds		
Playback	Multi Decoding		1, 4	1, 4, 8	1, 4, 8, 9, 16
	Playback Speed	Single Channel FF/FR	x0.25, x0.5, x2, x4, x8, x16, x32, x64, x128		
		Multi Channel FF/FR	x0.25, x0.5, x2, x4, x8, x16, x32, x64, x128		
	Search Mode		Timeline, Event, Archive, Log, Specific Time		
Storage	HDD	Interface	Serial ATA		
		Capacity of 1 HDD	2 TB		
		Internal HDD	1 EA (2 EA w/o ODD)	1 EA (2 EA w/o ODD)	2 EA (4 EA w/o ODD)
		S.M.A.R.T	HDD Error Check and Reporting using by Alarm and e-Mail		
	External Storage		1 eSATA		
	File System		Self-developed, Reliable and Stable File System		
Backup	Format	JPEG, AVI and H.264			
	Media	USB Flash Drive, USB External HDD, Netw ork			
User Interface	Menu Display		GUI (Graphic User Interface)		
	Input Method		Mouse, IR Remote Control		
Serial Port	Console & POS		1 RS-232C (D-sub 9pin)		
	PTZ & Keyboard Control		1 RS-485	1 RS-485	2 RS-485
Network	Dynamic DNS		Free DDNS		
	Streaming		RTP, RTSP		
	Netw ork Interface		RJ-45, 10/100/1000 Base-T		
	Dual Netw ork Streaming		640x360@120fps or 320x180@120fps>		
Network Access	Web view er (1:1)		Live, Search, Backup, PTZF, Remote Setup, Remote Upgrade		
	3G Mobile View er (1:1)		Live, Search, PTZF		
	Client Softw are (1:1)		Live, Search, Backup, PTZF, Remote Setup, Remote Upgrade		
	CMS (1:N)		Live, Search, Backup, PTZF, Remote Setup, Remote Upgrade		
Features	DLS (Day Light Saving)		YES		
	Internal Beep		By Alarm, Motion, Video Loss, HDD Error		
	Multi Language		Yes		
	Softw are Upgrade		By USB Flash Drive, Netw ork Remote Upgrade		
	NTP (Netw ork Time Protocol)		YES		
	Digital Zoom		YES		
	Remote Setup		YES		
General	Operation Condition		5°C~40°C (41°F~104°F), Humidity 20~80%		
	Pow er		DC 12V 5A		AC 100~120V/200~240V, 50/60Hz, 280W
	Net Weight (Gross Weight)		4.1Kgs (6.2Kgs)		6.8 kg (9.0 kg) / 15.0 lbs (19.8 lbs)
	Unit Dimension (W x D x H)		380mm x 340mm x 72mm		432mm x 430mm x 98mm (17.00" x 16.92" x 38.58")