

DH-HCVR5424/5432L

24/32CH 720P 1.5U HDCVI DVR



Features

- > Up to 24/32 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > HCVR5424/5432L: All channel 720P
- > 2HDMI/VGA/TV simultaneous video output
- > 16 channel synchronous realtime playback, GRID interface & smart search
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 4 SATA HDDs up to 16TB, 1 eSATA up to 16TB, 3 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-HCVR5424/5432L


Technical Specifications

Model		DH-HCVR5424L		DH-HCVR5432L	
System					
Main Processor		Embedded processor			
Operating System		Embedded LINUX			
Video					
Input		24 channel, BNC		32 channel, BNC	
Standard		NTSC(525Line, 60f/s), PAL(625Line, 50f/s)			
Audio					
Input		4 channel, BNC			
Output		1 channel, BNC			
Two-way Talk		1 channel Input,1 channel Output, BNC			
Display					
Interface		2 HDMI, 1 VGA, 1 TV			
Resolution		1920×1080, 1280×1024, 1280×720, 1024×768, 800×600			
Display Split		1/4/8/9/16/25		1/4/8/9/16/25/36	
Privacy Masking		4 rectangular zones (each camera)			
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording			
Recording					
Video/Audio Compression		H.264/G.711			
Resolution		720P(1280×720)/960H(960×576/960×480)/D1/4CIF(704×576/704×480)/CIF(352×288/352×240)/QCIF(176×144/176×120)			
Record Rate	Main Stream:	720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)			
	Extra Stream	CIF/QCIF(1~25/30fps)			
Bit Rate		48~8192Kb/s			
Record Mode		Manual, Schedule(Regular(Continuous), MD), Stop			
Record Interval		1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec			
Video Detection & Alarm					
Trigger Events		Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips			
Video Detection		Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank			
Alarm Input		16 channel			
Alarm Output		6 channel			
Playback & Backup					
Sync Playback		1/4/8/16			
Search Mode		Time/Date, MD & Exact search (accurate to second)			
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom			
Backup Mode		USB Device/eSATA Device/Internal SATA burner/Network			

DH-HCVR5424/5432L

Network	
Ethernet	RJ-45 port (10/100M/1000M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	4 SATA ports, up to 16TB
External HDD	1 eSATA port (Max 4 SATA HDDs), up to 16TB
Auxiliary Interface	
USB Interface	3 ports (2 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port RS485 for PTZ control, 1 port RS422 for Keyboard
General	
Power Supply	AC 100~240 V, 50/60 Hz
Power Consumption	40W
Working Environment	-10°C ~ +55°C / 10%~90%RH / 86~106kpa
Dimension(W×D×H)	1.5U, 440mm×410mm×71mm
Weight	6KG(without HDD)

System Connection



*Takes HCVR5432L as an example

Dahua Technology Co., Ltd.

1199' BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

DH-HCVR5424/5432L

*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.